# APPENDIX C UTILITIES

### **ACRONYMS, ABBREVIATIONS, AND SYMBOLS**

**7SFG(A)** 7th Special Forces Group (Airborne)

**96 CEG/CEVC** 96<sup>th</sup> Civil Engineer Group, Environmental Compliance Branch

**AFB** Air Force Base

**AWWA** American Water Works Association

**gpd** Gallons per Day

IJTS Initial Joint Training Site
JSF Joint Strike Fighter

USEPA U.S. Environmental Protection Agency

Appendix C Utilities

1 UTILITIES

## 2 CALCULATIONS USED TO ESTIMATE POTABLE WATER USE AND 3 WASTEWATER

#### **4 Potable Water**

Estimates of potable water use are based on the number of personnel expected to be affiliated with the Joint Strike Fighter (JSF) Initial Joint Training Site (IJTS). The number of personnel is multiplied by coefficients that represent the gallons consumed on average and at a maximum per person per day at Eglin Air Force Base (AFB). The coefficients are based on actual and projected consumption and population estimates for Eglin AFB and were derived by the Eglin Environmental Compliance office

11 (96 CEG/CEVC).

1213

14

15

16

17

18

The coefficients may overestimate the number of gallons expected to be consumed. However, the potable water estimates are based solely on the number of personnel. They do not incorporate water use by equipment or industrial processes, such as the two freshwater rinses and aircraft wash rack proposed for the JSF aircraft. The reason for this is industrial water use has not been quantified enough to develop a valid coefficient. By using the higher multiplier, the various industrial uses of water are accounted for in initial analysis, providing more flexibility later in the planning process.

192021

#### Potable water estimates:

2223

Number of personnel × coefficient = gallons per day (gpd)

2425

Average maximum per capita use: coefficient = 231 gallons/person/day

2627

No Action Alternative and Alternatives 1A and 1I:

28 29

2,481 (number of JSF IJTS personnel) × 231 gallons = 572,785 gpd

30 31

Alternatives 2A, 2B, 2C, 2D, and 2E:

32 33

1,203 (number of JSF IJTS personnel located at Eglin Main Base) × 231 gallons = 277,735 gpd

= 277,735 gp

1,278 (number of JSF IJTS personnel located at Duke Field) × 231 gallons = 295,050 gpd

37

Utilities Appendix C

#### 1 Wastewater

2 A combination of methods outlined in the U.S. Environmental Protection Agency's

- 3 (USEPA) Onsite Wastewater Treatment Systems Manual (USEPA, 2002) and the American
- 4 Water Works Association (AWWA, 2006) website were used to estimate wastewater
- 5 rates for the JSF IJTS and the 7th Special Forces Group (Airborne) (7SFG[A]).
- 6 Wastewater estimates can be based on either number of personnel inhabiting certain
  - predefined facilities or the square footage of structures.

7 8

- 9 The Onsite Wastewater Treatment Systems Manual (USEPA, 2002) categorizes facilities and
- 10 estimates typical wastewater flow rates per unit. For example, an office has a typical
- 11 wastewater flow rate of 13 gallons per employee per day. However, a dining hall
- measures typical wastewater flow rates per meal served based on a figure of 7 gallons
- per meal per day.

14

- 15 After estimating wastewater flow rates for each facility, each amount was added to
- 16 calculate the total wastewater flow rates expected from the JSF IJTS. Square footage
- 17 was used as the basis for estimating typical wastewater flow rates when the type of
- 18 facility was not included in the USEPA's report or when the number of units could not
- 19 be accurately estimated.

202122

- Examples of estimating flow rate by facility:
- Wastewater flow rates for JSF IJTS personnel working on a daily basis under the No Action Alternative and Alternatives 1A and 1I:

25

- 26 2,481 (number of personnel) × 13 gallons/person/day in office or industrial facility = 32,253 gpd.
- 28 (Note: the typical flow rate for industrial facilities accounts for sanitary 29 waste only and does not include wastewater produced by industrial 30 processes.)

31

Wastewater flow rates for JSF IJTS personnel living in the dormitories on a daily basis:

323334

35

732 pilot and maintainer students × 40 gallons/person/day = 29,280 gpd

#### REFERENCES

- 36 American Water Works Association (AWWA), 2006. Industrial, Commercial and Irrigation Demand and
- Contribution to Wastewater Flow. Retrieved from http://www.awwa.org/waterwiser/watch/
- index.cfm?ArticleID=210, on 29 August 2006.
- 39 U.S. Environmental Protection Agency (USEPA), 2002. *Onsite Wastewater Treatment Systems Manual* 40 (EPA/625/R-00/008). Office of Water, Office of Research and Development. February 2002.